



# High Quality Transformers

No	品番	1次電圧 (V)	2次電圧 (V±5%)	2次電流 (A)	電力 (VA)	試作時実測参考データ (at 50Hz)						
						無負荷電圧 (V±5%)	電圧変動率 (±30%)	励磁電流 (mA±50%)	入力電流 (mA±35%)	外形構造	重量 (約 gr)	温度上昇 (前後)
35	P1-122	0-100-110	0-6-10-12	2.0	24	0-6.8-11.3-13.8	11.3	67	315	FH6030BR	720	定 49/44°C
36	P1-241	0-100-110	0-6-12-24	1.0	24	0-6.9-13.6-27.1	9.7	57	315	FH6030BR	720	
37	P1-301C	100	0-9-15-30	1.0	30	0-9.9-16.7-33.4	9.35	58	375	FH6030BR	720	定+10% 45/58°C
38	P1-5005	0-100-110	0-40-45-50	0.50	25	2-45.2-51-56.2	10.6	56	318	FH6030BR	720	
39	P1-123B	100	0-12	3.0	36	0-13.1	9.22	70	440	FH6630BR	890	
40	P1-123S	100	0-12	3.0	36	0-13.3	9.0	70	485	FH6630BR	890	定 48/52°C
41	P1-2015A	100	0-20	1.5	30	0-22.0	9.5	48	365	FH6630BR	890	定+10% 35/44°C
42	P1-123	0-100-110	0-6-10-12	3.0	36	0-6.7-11-13.4	10.7	65	485	FH6630BR	890	
43	P1-301	0-100-110	0-21.6-27-33	1.0	30	0-21.6-27-33	9.3	76	370	FH6630BR	890	
44	P1-301D	100	0-9-15-30	1.0	30	0-9.7-16.4-32.8	9.8	67	365	FH6630BR	890	定+10% 44/52°C
45	P1-202	0-100-110	0-16-18-20	2.0	40	0-17.5-19.8-21.9	9.5	55	475	FH6635BR	1010	
46	P1-381	0-100-110	0-32-35-38	1.0	38	0-35.1-38.3-41.6	9.5	61	460	FH6635BR	1010	
47	P1-1625	100	0-16	2.5	40	0-17.3	7.5	52	470	FH7630BR	1300	
48	P1-1635	100	0-16	3.0	48	0-17.6	10	50	560	FH7630BR	1300	
49	P1-242L	100	0-24	2.0	48	0-26.0	7.4	46	553	FHB7630BL	1300	定+10% 33/41°C
50	P1-242	0-100-110	0-6-12-24	2.0	48	0-6.5-13.1-26.2	8.3	57	560	FH7630BR	1300	
51	P1-501	0-100-110	0-40-45-50	1.0	50	0-44-49.5-55	8.9	85	595	FH7630BR	1300	
52	P1-124	100	0-12	4.0	48	0-12.8	6.8	58	555	FHB7635BR	1400	+10% 53/62°C
53	P1-163VCL	100	0-16	3.0	48	0-17.3	7.2	68	553	FVC7635VBL	1400	
54	P1-242BF	100 ( f付)	0-24	2.0	48	0-26.2	7.4	60	565	FH7635BL	1400	定+10% 47/51°C
55	P1-2425	100 ( f付)	0-24	2.5	60	0-25.9	7.1	68	670	FHB7635BR	1400	定+10% 55/65°C
56	P1-2425SU	100 ( f付)	0-24	2.5	60	0-26.4	8.7	98	712	FL7635BR	1400	定+10% 53/60°C
57	P1-2425SG	100 ( f付)	0-24	2.5	60	0-26.6	9.9	93	692	FL7635BR	1400	定+10% 39/50°C
58	P1-2425G	100 ( f付)	0-24	2.5	60	0-26.1	7.4	55	670	FHB7635BR	1400	定+10% 42/53°C
59	P1-125AU	100	0-12	5.0	60	0-12.8	6.7	85	695	FHB7640BR	1530	定+10% 47/60°C
60	P1-125BU	100 ( f付)	0-12	5.0	60	0-12.8	6.7	63	680	FH8635BR	1750	定+10% 38/43°C
61	P1-125BG	100 ( f付)	0-12	5.0	60	0-12.8	6.7	60	665	FH8635BR	1750	定+10% 25/34°C
62	P1-1245LU	100 ( f付)	0-12	4.5	54	0-12.7	6.4	42	595	FH8635BL	1750	定+10% 37/48°C
63	P1-1245LG	100 ( f付)	0-12	4.5	54	0-12.9	7.5	63	617	FH8635BL	1750	定+10% 31/39°C
64	P1-244SU	100 ( f付)	0-24	4.16	100	0-26.4	7.3	130	1160	SA8550	2450	定+10% 47/54°C
65	P1-244SG	100 ( f付)	0-24	4.16	100	0-26.5	6.9	120	1130	SA8550	2450	定+10% 36/44°C
66	P1-125D	0-100-110 ( f付)	0-12	5.0	120	0-12.7	5.4	175	1390	SI9655	3850	定+10% 43/63°C

