

VP1	VP2	VP3	VP0	AP1	AP2	AP3	AP0	WP	PF	Vs1	Vs2	Vs3	Vs0	As1	As2	As3	As0	VS0 AS0	VP0 AP0	η	ε	Temp-up
(V)	(V)	(V)	(V)	(mA)	(mA)	(mA)	(mA)	(W)		(V)	(V)	(V)	(V)	(mA)	(mA)	(mA)	(mA)	(VA)	(VA)	(%)	(%)	°C

⑦ 3E△△ 60-11U 3φ:3φ 200V:100V 0.27A (46.7 VA 目安) 測定(6)EI型△:△ 外形 FH 6025BR x 3 図

202.1	202.1	203.1	202.6	33.79	32.59	34.42	33.77	6.62	0.4825	109.3	109.1	109.6	109.6	0	0	0	0					
202.2	203.3	202.3	202.5	168.2	168.1	168.4	168.1	58.33	0.9882	99.94	100.5	99.85	100.2	272.9	273.4	272.5	272.7	47.36	58.98	80.29	(9.3)	38/33
223.7	224.8	224.1	223.4	42.59	40.69	43.32	43.11	8.13	0.4225	121.2	121.9	121.6	121.1	0	0	0	0					
224.0	224.6	224.1	224.7	189.0	188.5	188.4	188.6	72.33	0.9841	111.0	111.7	111.3	111.5	306.1	306.2	305.7	304.8	58.92	73.43	80.23	(8.6)	44/43
243.0	243.6	243.8	243.9	54.43	52.40	55.52	54.82	9.77	0.3657	132.2	132.3	132.6	132.4	0	0	0	0	0				
243.8	244.6	243.7	244.2	215.3	212.9	215.3	214.1	88.97	0.9814	119.2	119.6	119.1	119.4	347.4	347.0	347.6	347.7	71.91	90.56	79.40	(10.8)	48/48
265.3	266.4	266.1	266.0	83.29	77.27	84.52	84.96	12.21	0.2731	143.8	144.6	143.9	143.9	0	0	0	0					
265.2	265.5	264.9	265.2	235.1	233.4	235.6	234.4	103.8	0.9738	129.3	129.9	129.4	129.7	373.8	375.5	374.1	374.8	84.25	107.7	78.19	(10.9)	53/55

⑧ 3E△△ 60-11G 3φ:3φ 200V:100V 0.295A (51.0 VA 目安) 測定(6)EI型△:△ 外形 FH 6025BR x 3 図

204.3	204.5	205.0	203.7	21.78	22.14	21.98	21.87	1.55	0.1736	110.0	109.7	110.5	110.2	0	0	0	0					
204.8	204.8	204.1	204.4	166.6	166.5	167.1	167.0	58.86	0.9934	101.3	101.5	101.2	101.6	296.8	295.4	296.3	296.3	52.16	59.13	88.22	(8.5)	26/24
221.1	221.2	221.6	221.7	32.95	33.25	33.36	32.98	2.09	0.1406	121.0	121.7	121.3	121.0	0	0	0	0					
221.8	222.8	221.1	222.2	184.1	183.3	184.3	183.9	69.66	0.9889	109.9	110.4	109.6	110.1	324.5	324.3	324.8	324.8	61.94	70.80	87.47	(10.0)	31/26
243.1	243.6	243.9	243.5	47.42	48.41	48.72	48.48	2.93	0.1225	132.1	132.9	133.4	132.7	0	0	0	0					
243.7	244.1	243.1	243.8	209.2	209.2	209.4	209.1	86.29	0.9823	119.6	120.0	119.5	119.9	365.1	366.1	366.3	366.7	76.15	88.33	86.20	(10.7)	38/35
263.8	265.5	264.3	263.7	67.38	67.48	68.75	68.01	4.01	0.1127	143.2	144.2	143.8	143.6	0	0	0	0					
264.0	265.0	264.3	264.5	229.3	229.3	229.9	229.9	102.4	0.9727	130.0	130.0	129.6	127.7	398.5	397.4	397.6	398.1	89.50	105.3	84.96	(10.8)	43/41

⑨ 3EYY 60-11U 3φ:3φ 210V:100V 0.3A (51.9 VA 目安) 測定(5)EI型Y:Y 外形 FH 6025BR x 3 図

214.3	214.9	214.6	214.7	35.73	35.16	36.56	36.06	6.86	0.4438	116.8	116.9	116.9	116.8	0	0	0	0					
214.0	214.5	214.7	215.8	184.5	184.5	185.7	183.5	67.40	0.9895	106.9	106.6	106.3	106.4	303.2	302.7	302.8	302.5	55.78	68.62	81.29	(9.8)	40/35
236.3	237.1	237.3	236.9	45.20	45.13	46.63	45.58	8.10	0.3784	128.7	129.1	129.2	128.8	0	0	0	0					
236.5	236.6	236.7	236.4	206.3	206.8	208.7	207.1	83.18	0.9852	117.6	117.4	117.6	117.3	337.6	337.2	337.7	337.9	68.66	84.80	80.99	(9.8)	46/43
254.8	256.0	255.9	255.7	57.07	56.21	59.18	58.10	9.57	0.3218	139.0	140.2	140.1	139.9	0	0	0	0					
254.6	256.2	255.0	255.0	231.8	232.7	235.0	233.8	101.6	0.9824	125.7	126.0	125.6	125.6	384.0	383.3	383.4	383.8	83.57	103.3	80.87	(11.4)	56/53
272.6	274.0	273.4	273.2	70.67	70.08	73.26	71.96	11.08	0.2829	148.7	149.5	149.0	149.0	0	0	0	0					
272.5	272.3	273.5	272.5	247.4	251.7	251.6	250.0	115.8	0.9775	133.1	133.0	133.0	133.2	407.5	410.1	407.3	408.5	94.29	118.0	79.89	(11.9)	60/59

⑩ 3EYY 60-11G 3φ:3φ 210V:105V 0.3A (54.5 VA 目安) 測定(5)EI型Y:Y 外形 FH 6025BR x 3 図

211.5	211.8	212.0	211.6	18.03	18.33	18.40	18.30	1.69	0.2234	115.5	115.4	115.8	115.7	0	0	0	0					
211.1	211.3	210.1	210.8	166.7	167.9	167.2	167.8	61.55	0.9970	105.9	106.1	105.4	105.8	296.9	299.6	297.8	297.5	54.56	62.04	87.94	(9.4)	26/24
234.9	235.6	235.8	235.1	31.54	32.13	32.33	32.12	2.23	0.1483	128.2	129.3	129.5	129.4	0	0	0	0					
235.2	235.7	235.0	236.1	187.2	188.8	188.3	188.3	76.17	0.9906	118.0	118.1	117.4	117.8	330.2	333.5	331.0	331.8	67.75	77.00	87.98	(9.9)	32/30
257.4	259.0	258.4	257.7	47.13	47.01	47.90	47.78	2.95	0.1195	140.5	141.1	140.7	140.7	0	0	0	0					
257.1	257.9	257.8	257.4	221.7	222.2	222.5	222.5	97.98	0.9860	127.3	127.9	127.6	127.7	388.4	388.9	389.0	389.3	86.14	99.24	86.80	(10.2)	40/42
272.7	275.7	274.2	273.9	60.62	59.56	60.59	60.47	3.53	0.1082	148.8	148.8	148.3	147.8	0	0	0	0					
272.3	272.9	272.8	273.0	235.7	236.9	234.9	236.4	109.1	0.9813	134.6	134.6	134.8	134.7	140.1	412.0	410.1	411.1	95.98	111.8	85.81	(9.8)	46/46