

VP1	VP2	VP3	VP0	AP1	AP2	AP3	AP0	WP	PF	Vs1	Vs2	Vs3	Vs0	As1	As2	As3	As0	Vs0 AS0	VP0 AP0	η	ε	Temp-up
(V)	(V)	(V)	(V)	(mA)	(mA)	(mA)	(mA)	(W)		(V)	(V)	(V)	(V)	(mA)	(mA)	(mA)	(mA)	(VA)	(VA)	(%)	(%)	°C

① 3EΔY48-11U 3φ:3φ 210V:100V 85mA (14.7 VA 目安) 測定(8)E I 型 Δ:Y 外形 FH 4816BR x 3 図

200.3	201.2	200.0	200.5	13.44	13.14	13.71	13.37	2.54	0.5492	109.1	109.1	108.7	108.9	0	0	0	0					
211.0	211.7	210.1	210.8	57.01	57.27	57.61	57.53	20.71	0.9829	100.0	100.9	100.7	100.7	90.19	89.68	89.73	89.77	15.66	21.01	74.57	(13.9)	26/25
220.0	221.2	220.5	221.3	16.86	16.27	17.18	16.80	3.07	0.4790	120.0	120.7	120.3	120.5	0	0	0	0					
230.9	231.1	230.7	231.2	64.65	64.56	65.53	64.96	25.47	0.9779	109.3	110.2	109.7	109.6	101.0	101.5	101.7	101.6	19.29	26.01	74.18	(15.5)	30/25
240.7	241.6	240.8	240.8	21.03	20.17	21.30	20.81	3.68	0.4241	130.8	131.1	130.7	131.0	0	0	0	0					
254.0	254.1	254.6	254.9	77.78	77.51	78.43	77.86	33.53	0.9753	118.1	118.1	117.7	118.2	122.9	122.5	122.6	122.6	25.10	34.33	73.03	(17.7)	40/39
260.4	260.7	260.0	260.5	28.34	27.00	28.60	27.95	4.51	0.3579	141.5	141.9	142.1	141.9	0	0	0	0					
273.3	273.8	274.0	272.8	84.60	85.18	85.51	84.97	40.03	0.9620	128.0	127.9	128.0	127.5	134.9	137.2	134.1	134.3	29.68	40.15	73.94	(16.7)	46/45

② 3EΔY48-11G 3φ:3φ 210V:100V 85mA (14.7 VA 目安) 測定(8)E I 型 Δ:Y 外形 FH 4816BR x 3 図

201.2	200.6	200.1	200.7	7.87	7.66	7.99	7.85	0.71	0.2610	109.6	110.0	110.2	110.1	0	0	0	0					
212.5	212.0	212.2	212.5	49.75	49.77	50.40	50.16	18.26	0.9882	103.0	103.1	102.8	103.0	86.16	86.20	86.15	86.26	15.39	18.46	83.37	(13.5)	16/16
241.1	240.8	240.4	240.7	16.88	16.58	17.23	16.80	1.26	0.1797	132.2	132.2	131.8	131.8	0	0	0	0					
243.5	243.3	243.2	243.7	62.01	62.62	62.55	62.70	25.85	0.9771	116.8	116.9	116.6	116.5	106.4	106.3	106.3	106.0	21.42	26.47	80.92	(14.5)	22/23
257.7	258.4	258.3	257.9	22.73	22.62	23.94	23.58	1.72	0.1415	141.5	141.8	142.3	142.1	0	0	0	0					
257.6	258.3	258.1	257.2	83.78	83.94	84.42	84.19	37.16	0.9835	116.9	117.0	116.9	116.7	144.9	145.4	145.8	145.1	29.34	37.50	78.24	(21.7)	33/38
273.1	274.3	274.5	273.9	30.65	29.84	31.24	30.94	2.27	0.1347	149.2	149.9	150.3	149.8	0	0	0	0					
272.7	272.3	273.0	272.4	89.28	89.67	89.72	87.69	41.40	0.9776	123.5	123.1	123.0	123.8	153.3	153.5	153.1	153.4	32.91	42.32	77.76	(21.0)	38/42

③ 3EYΔ54-10U 3φ:3φ 210V:20V 0.94A (32.5 VA 目安) 測定(7)E I 型 Y:Δ 外形 FH 5421BR x 3 図

200.3	200.2	200.4	200.6	20.85	21.58	20.81	20.93	4.44	0.6069	22.36	22.27	22.28	22.30	0	0	0	0					
208.7	208.6	208.4	209.1	119.1	118.2	118.1	118.4	42.40	0.9904	20.75	20.66	20.63	20.07	0936A	0940A	0937A	0939A	33.64	42.90	78.41	(11.1)	37/34
231.1	230.5	230.8	231.4	28.29	28.89	27.59	28.62	5.88	0.5128	25.68	25.65	25.68	25.67	0	0	0	0					
230.2	230.8	230.8	230.8	131.4	131.3	130.1	130.9	51.79	0.9873	22.81	22.80	22.73	22.80	1.035A	1.035A	1.035A	1.035A	40.92	52.34	78.17	(12.5)	42/39
250.4	251.2	250.2	250.6	36.45	37.52	36.19	36.70	7.05	0.4449	29.90	27.90	27.76	27.93	0	0	0	0					
253.4	253.1	253.4	253.8	144.3	143.9	142.5	143.7	61.64	0.9832	24.95	24.91	24.92	24.89	1.132A	1.133A	1.128A	1.134A	48.92	63.20	77.40	(13.9)	50/47
270.7	271.3	270.8	270.9	57.39	58.92	57.42	58.06	8.78	0.3210	30.17	30.14	30.13	30.16	0	0	0	0					
275.7	275.0	275.7	275.0	159.9	159.4	158.1	158.9	72.98	0.9693	26.85	26.90	26.99	26.97	1.232A	1.235A	1.232A	1.239A	57.89	75.90	76.27	(13.8)	58/57

④ 3EYΔ54-10G 3φ:3φ 210V:21V 0.89A (32.3 VA 目安) 測定(7)E I 型 Y:Δ 外形 FH 5421BR x 3 図

209.1	209.3	209.8	208.8	19.30	17.94	18.43	18.63	1.26	0.1584	23.37	23.38	23.44	23.38	0	0	0	0					
209.1	209.3	209.0	208.4	104.8	104.3	103.8	104.1	37.56	0.9914	21.03	21.05	21.02	21.03	0.8962	0.8985	0.8904	0.8976	32.69	37.59	86.96	(11.2)	20/18
230.5	230.0	230.6	230.3	28.69	26.78	27.25	28.10	1.75	0.1331	25.75	25.81	25.79	25.70	0	0	0	0					
230.2	230.0	230.2	230.9	116.2	115.3	115.6	116.1	45.1	0.9841	23.09	23.29	23.23	23.15	0.9902	0.9912	0.9867	0.9906	39.73	46.47	85.50	(11.1)	25/21
247.4	248.9	248.3	247.7	38.20	35.50	36.74	37.31	2.25	0.1226	27.69	27.70	27.56	27.59	0	0	0	0					
247.1	247.1	247.4	247.5	126.9	125.8	126.4	126.9	53.2	0.9751	24.86	24.90	24.91	24.80	1.0581	1.0571	1.0578	1.0575	45.43	54.43	83.46	(11.3)	30/25
265.9	266.3	266.9	266.2	50.02	47.21	49.04	49.14	2.95	0.1150	29.64	29.63	29.61	29.59	0	0	0	0					
265.9	266.4	266.5	265.7	139.0	137.7	138.5	138.2	61.41	0.9626	26.54	26.62	26.62	26.64	1.1421	1.1403	1.1413	1.1414	52.68	62.24	84.63	(11.1)	35/30